

PVC FLEXIBLE SUCTION HOSE COUPLED FEMALE LONG HANDLE X MALE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/07/2026 07:26 PM

SKU

: 27520

BRAND

: DIXON VALVE

MODEL

: FSH-9682-500

Use:

Designed for drafting use only

Features:

With the most advanced collar attachment in the industry, Dixon Northline's Suction Hose is far superior to others in the industry. The collar is made from durable lightweight plastic, molded four inches wide. With the length of the shank on the coupling, inserted into the hose and the width of the collar combined, the chance of leakage is minimal when the hose is flexed while in use.

Industry's lightest flexible suction hose. The suction hose design incorporates engineered polymers and extruded aluminum parts to maximize strength, durability and performance.

Construction:

Hose is made of flexible PVC and lightweight for ease of operation. Its black helix design allows for easier maintenance and UV protection. Clear PVC provides a view of water flow and assists in obtaining prime.

Hose collars has a high performance injection molded polymer design to ensure a 360° seal. The high-tech polymer material offers durability and reduces overall hose weight up to 12%. The flexible design allows for quick and easy in field serviceability with a 1/4" socket wrench.

Aluminum couplings hose ends are made from 6061-T6 lightweight structural aluminum alloy for maximum strength and durability. The threaded couplings are finished black anodized and laser engraved with a clear understanding of the thread type and size being provided. Swivels are attached using roller "disc" bearings for maximum performance and sheer strength. Supplied as long handle style.

Available Options:

Consult Dixon for pricing and availability of smaller and larger diameters, other lengths, threads and configurations.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|--------------|
| Maximum Operating Pressure | 35 PSI |
| Factory Part Number | FSH-9682-500 |
| Size | 6" |
| Thread | NST (NH) |
| Weight Lb | 58.0000 |