

## EZ-CEPT OVERFILL DOUBLE SOCKET



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/20/2026 12:30 PM

SKU

: 14018

BRAND

: DIXON VALVE

MODEL

: FT390G

### Features:

Optic 6 pin, 3 J-slot, and thermistor 10 pin, 4 J-slot, horizontal mount, GFL stainless J slot wear rings, internal ground wire (U.S.)

Sockets and caps are color coded with industry standardized colors which allows for easy identification of socket type (optic sockets are blue, thermistor sockets are green, and float sockets are red, colored caps are included for optic and thermistor models only).

Guaranteed for Life J-Slots: Our unique stainless steel alloy J-slot ring will probably outlast your trailer.

Prewired ready for tank installation, no more long hours wiring and troubleshooting your socket connections. Simply bolt to the trailer and connect to the terminal block in the on board monitor.

Ground bolt and ID chip ready: Both ground bolt and ID chip are normally mounted inside the EZ-Cept housing to protect from the corrosive elements. Or if desired, the bolt can be mounted to the trailer frame and the wire connected to the EZ-Cept internal wire terminal.

Patented, the EZ-Cept has so many innovative features it is covered by US patent 6,824,423.

### Construction:

Corrosion resistant hard powder coated housing, stainless steel hardware and contacts and our unique keep dry enclosure design keeps your trailer in service and corrosion at bay. Take a close look at FloTech EZ-Cept- we challenge you to find a better constructed API socket on the market.

Stainless steel hardware and contact pins prevent corrosion

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Description</b>	Optic 5 pin and 3 J slots; Thermistor 10 pin and 4 J slots (U.S.)
<b>Includes</b>	Internal ground wire
<b>Mount</b>	Horizontal
<b>Factory Part Number</b>	FT390G
<b>Weight Lb</b>	6.1100