

GLOBAL CRIMP STYLE CAM & GROOVE TYPE C COUPLER X HOSE SHANK



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/23/2026 04:25 PM

SKU
: 24325

BRAND
: DIXON VALVE

MODEL
: G150-C-ALCR

Use:
Designed for use with liquids, consult Dixon for specific recommendations
Suitable for use with King Crimp sleeves and ferrules

Features:
Safety clips and a Buna-N gasket included

Available Options:
Other gasket types are available, contact Dixon.

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	G150-C-ALCR
Material	A380 Permanent Mold Aluminum
Seal	Buna-N
Size	1-1/2"
Weight Lb	0.8100
Working Pressure	250 PSI