

## GLOBAL CRIMP STYLE CAM & GROOVE TYPE C COUPLER X HOSE SHANK



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/23/2026 04:25 PM

SKU  
: 24339

BRAND  
: DIXON VALVE

MODEL  
: G300-C-ALCR

Use:  
Designed for use with liquids, consult Dixon for specific recommendations  
Suitable for use with King Crimp sleeves and ferrules

Features:  
Safety clips and a Buna-N gasket included

Available Options:  
Other gasket types are available, contact Dixon.

Safety notes:  
Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	G300-C-ALCR
<b>Material</b>	A380 Permanent Mold Aluminum
<b>Maximum Operating Pressure</b>	125 PSI,  150 PSI with King Crimp Ferrule system
<b>Seal</b>	Buna-N
<b>Size</b>	3"
<b>Weight Lb</b>	1.9000