

GLOBAL CRIMP STYLE CAM & GROOVE TYPE E ADAPTER X HOSE SHANK



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 01:09 PM

SKU
: 24344

BRAND
: DIXON VALVE

MODEL
: G300-E-SSCR

Use:
Designed for use with liquids, consult Dixon for specific recommendations
Suitable for use with King Crimp® sleeves and ferrules

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

Only use the crimp style shanks with the crimp style sleeves and ferrules. Due to differences in dimensions and tolerances for safety reasons, do not interchange other manufacturer's products with Dixon products.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	G300-E-SSCR
Material	316 Investment Cast Stainless Steel
Maximum Operating Pressure	125 PSI, 150 PSI with King Crimp Ferrule system
Size	3"
Weight Lb	4.0100