

## GLOBAL AIR KING® 2-LUG MALE NPT ENDS



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/10/2026 04:51 PM

SKU

: 14548

BRAND

: DIXON VALVE

MODEL

: GAM12

Use:

Use of supplied safety clip guarantees the fittings are properly connected because the safety pin will not go through the holes in mating fittings until couplings are locked in place. Only one Air King safety clip or wire type retainer is required for each Air King universal coupling.

Air King is for air and water service only

Specifications:

Air King meets pressure requirements as specified in A-A-59553 commercial item description superseding Mil Spec.WWC-633D.

Features:

Safety clip included

Supplied with rubber washer, part # AWR4

Safety notes:

Air King is for air and water service only

Never use any Air King coupling for steam service!

The use of an Air King safety clip or wire type retainer is necessary to ensure Air King universal couplings will not become accidentally disconnected.

To provide protection against coupling breakage and related hazards, Dixon recommends the use of a whip hose.

Pressure rating given at ambient temperature 70°F/21°C

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	GAM12
<b>Material</b>	Plated Steel
<b>Pressure Rating</b>	150 PSI at 70°F (21°C)
<b>Seal</b>	Rubber
<b>Size</b>	1"
<b>Weight Lb</b>	0.5300