

BRASS STANDARD DRY GAUGE



DATE
: 04/17/2026 01:32 AM

SKU
: 14563

BRAND
: DIXON VALVE

MODEL
: GBR100

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.100 Grade B ($\pm 3/2/3\%$ accuracy)

Construction:

- Copper alloy bourdon tube
- 1/4" lower mount
- Polished brass case
- Polished brass ring
- Copper alloy bourdon tube

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GBR100
Figure Interval	20
Material	Brass
Minor Gradient	2
Mount	1/4" lower mount
Pressure Range	0-100 PSI

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Size	2-1/2" Face
Temperature Range	-40°F to 140°F (-40°C to 60°C)
Weight Lb	0.3400