

BRASS STANDARD DRY GAUGE



DATE
: 07/08/2026 07:05 AM

SKU
: 14564

BRAND
: DIXON VALVE

MODEL
: GBR1000

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.100 Grade B ($\pm 3/2/3\%$ accuracy)

Construction:

- Copper alloy bourdon tube
- 1/4" lower mount
- Polished brass case
- Polished brass ring
- Copper alloy bourdon tube

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GBR1000
Figure Interval	200
Material	Brass
Minor Gradient	20
Mount	1/4" lower mount
Pressure Range	0-1000 PSI

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Size	2-1/2" Face
Temperature Range	-40°F to 140°F (-40°C to 60°C)
Weight Lb	0.3225