

## BRASS STANDARD DRY GAUGE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 04/17/2026 01:34 AM

SKU  
: 14566

BRAND  
: DIXON VALVE

MODEL  
: GBR1500

### Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

### Specifications:

ASME B40.100 Grade B ( $\pm 3/2/3\%$  accuracy)

### Construction:

- Copper alloy bourdon tube
- Dual PSI / kPa scale dial
- Polished brass case
- Polished brass ring

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	GBR1500
<b>Figure Interval</b>	300
<b>Material</b>	Brass
<b>Minor Gradient</b>	20
<b>Mount</b>	1/4" lower mount
<b>Pressure Range</b>	0-1500 PSI
<b>Size</b>	2-1/2" Face

**TECHNICAL SPECIFICATIONS**

**Temperature Range** -40°F to 140°F (-40°C to 60°C)

**Weight Lb** 0.3235