

## BRASS STANDARD DRY GAUGE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 05:21 AM

SKU

: 14569

BRAND

: DIXON VALVE

MODEL

: GBR2000

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.100 Grade B ( $\pm 3/2/3\%$  accuracy)

Figure interval: 500

Gradient interval: 50

Construction:

Copper alloy bourdon tube

Dual PSI / kPa scale dial

Polished brass case

Polished brass ring

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	GBR2000
<b>Material</b>	Brass
<b>Mount</b>	1/4" lower mount
<b>Pressure Range</b>	0-2000 PSI
<b>Size</b>	2-1/2" Face
<b>Temperature Range</b>	-40°F to 140°F (-40°C to 60°C)
<b>Weight Lb</b>	0.3400