

**BRASS STANDARD DRY GAUGE**



DATE  
: 04/17/2026 01:33 AM

SKU  
: 14572

BRAND  
: DIXON VALVE

MODEL  
: GBR3000

Applications:  
All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:  
ASME B40.100 Grade B (± 3/2/3% accuracy)

Construction:  
Copper alloy bourdon tube  
Dual PSI / kPa scale dial  
Polished brass case  
Polished brass ring

Safety notes:  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	GBR3000
<b>Figure Interval</b>	500
<b>Material</b>	Brass
<b>Minor Gradient</b>	50
<b>Mount</b>	1/4" lower mount
<b>Pressure Range</b>	0-3000 PSI
<b>Size</b>	2-1/2" Face

\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Temperature Range</b>	-40°F to 140°F (-40°C to 60°C)
<b>Weight Lb</b>	0.3500