

WELDING GAUGE



* Referential image
 ** Some features may vary without prior notice. Sale subject to inventory availability

DATE
 : 04/23/2026 01:11 AM

SKU
 : 14579

BRAND
 : DIXON VALVE

MODEL
 : GBRW30

Applications:
 All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:
 ± 3-2-3% accuracy according to ASME B40.100 Grade B

Construction:
 Copper alloy bourdon tube
 "USE NO OIL" written in red on face
 Stainless steel case
 Twist-lock polycarbonate window
 Copper alloy bourdon tube

Safety notes:
 WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GBRW30
Figure Interval	5
Material	Brass
Minor Gradient	.5
Mount	1/4" lower mount
Pressure Range	0-30 PSI

TECHNICAL SPECIFICATIONS

Size	2-1/2" Face
Temperature Range	-40°F to 140°F (-40°C to 60°C)
Weight Lb	0.4380