

ABS STANDARD DRY GAUGE CENTER BACK MOUNT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 12:55 AM

SKU

: 14585

BRAND

: DIXON VALVE

MODEL

: GC200

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B (\pm 3-2-3% accuracy)

Features:

PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:

Polycarbonate window

Black aluminum pointer

ABS plastic case, corrosion resistant

C-shaped bronze safety bourdon tube

Center back mount

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GC200
Figure Interval	1
Minor Gradient	.5
Mount	1/4"
Pressure Range	0-15 PSI
Size	2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.1900