

COMPOUND GAUGE CENTER BACK MOUNT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/17/2026 03:28 AM

SKU

: 14587

BRAND

: DIXON VALVE

MODEL

: GC210

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B accuracy ($\pm 3-2-3$ % accuracy)

30" Mercury (Hg)

Features:

PowerFlex™ movement with polyester segment, designed for extended wear

Construction:

ABS plastic case, corrosion resistant

Bronze bourdon tube / brass socket

Polycarbonate window

Black aluminum pointer

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GC210
Figure Interval	30/20 (Hg/PSI)
Minor Gradient	5/5 (Hg/PSI)
Mount	1/4" Center Back Mount
Pressure Range	0-160 PSI
Size	2-1/2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.3000