

VACUUM GAUGE LOWER MOUNT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/22/2026 11:29 PM

SKU

: 14680

BRAND

: DIXON VALVE

MODEL

: GL105

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B accuracy ($\pm 3-2-3$ % accuracy)

30" Mercury (Hg)

Features:

PowerFlex™ movement with polyester segment, designed for extended wear

Construction:

ABS plastic case

Bronze bourdon tube

Polycarbonate crystal

Black aluminum pointer

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GL105
Figure Interval	5" (Hg/PSI)
Minor Gradient	.5" (Hg/PSI)
Mount	1/4" Lower Mount
Size	2" Face
Temperature Range	-40°F to 150°F (-40°C to 66°C)
Weight Lb	0.1750