

## COMPOUND GAUGE LOWER MOUNT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/17/2026 03:25 AM

SKU

: 14681

BRAND

: DIXON VALVE

MODEL

: GL110

### Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

### Specifications:

ASME B40.1, Grade B accuracy ( $\pm 3-2-3$  % accuracy)

30" Mercury (Hg)

### Features:

PowerFlex™ movement with polyester segment, designed for extended wear

### Construction:

ABS plastic case, corrosion resistant

Bronze bourdon tube / brass socket

Polycarbonate window

Black aluminum pointer

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	GL110
<b>Figure Interval</b>	30/20 (Hg/PSI)
<b>Minor Gradient</b>	10/10 (Hg/PSI)
<b>Mount</b>	1/4" Lower Mount
<b>Pressure Range</b>	0-160 PSI
<b>Size</b>	2-1/2" Face
<b>Temperature Range</b>	-40°F to 150°F (-40°C to 65.6°C)
<b>Weight Lb</b>	0.2500