

ABS STANDARD DRY GAUGE LOWER MOUNT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/16/2026 03:00 PM

SKU

: 14687

BRAND

: DIXON VALVE

MODEL

: GL140

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B (\pm 3-2-3% accuracy)

Features:

PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:

Polycarbonate window

Black aluminum pointer

ABS plastic case, corrosion resistant

C-shaped bronze safety bourdon tube

Lower mount

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GL140
Figure Interval	30
Minor Gradient	5
Mount	1/4"
Pressure Range	0-300 PSI
Size	2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.1700