

COMPOUND GAUGE LOWER MOUNT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 04/17/2026 03:26 AM

SKU
: 14691

BRAND
: DIXON VALVE

MODEL
: GL310

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B accuracy ($\pm 3-2-3$ % accuracy)
30" Mercury (Hg)

Features:

PowerFlex™ movement with polyester segment, designed for extended wear

Construction:

ABS plastic case, corrosion resistant
Bronze bourdon tube / brass socket
Polycarbonate window
Black aluminum pointer

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GL310
Figure Interval	30/10 (Hg/PSI)
Minor Gradient	5/2 (Hg/PSI)
Mount	1/4" Lower Mount
Pressure Range	0-100 PSI
Size	2-1/2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.2450