

## FLUTTERGUARD? DRY GAUGE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/21/2026 01:07 PM

SKU

: 14714

BRAND

: DIXON VALVE

MODEL

: GL365FG

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B ( $\pm$  3-2-3% accuracy)

Features:

FlutterGuard™ virtually eliminates pointer flutter, making the gauge easier to read and reducing excessive movement wear. Liquid-free casing results in lighter weight and eliminates the chance of gauge leakage.

PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:

ABS plastic case, corrosion resistant

Helical wound bronze safety bourdon tube (1000 PSI and higher)

Polycarbonate window

Black aluminum pointer

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	GL365FG
<b>Figure Interval</b>	400
<b>Minor Gradient</b>	50
<b>Mount</b>	1/4" Lower Mount
<b>Pressure Range</b>	0-2000 PSI
<b>Size</b>	2-1/2" Face
<b>Temperature Range</b>	-40°F to 150°F (-40°C to 65.6°C)
<b>Weight Lb</b>	0.2438