

ABS STANDARD DRY GAUGE LOWER MOUNT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 02:35 AM

SKU

: 14717

BRAND

: DIXON VALVE

MODEL

: GL375

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B (\pm 3-2-3% accuracy)

Features:

PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:

Polycarbonate window
Black aluminum pointer
ABS plastic case, corrosion resistant
Helical wound bronze safety bourdon tube
Lower mount

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GL375
Figure Interval	1000
Minor Gradient	100
Mount	1/4"
Pressure Range	0-5000 PSI
Size	2-1/2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.2400