

ABS STANDARD DRY GAUGE LOWER MOUNT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 04/16/2026 05:01 PM

SKU
: 14875

BRAND
: DIXON VALVE

MODEL
: GS160-4

Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

Specifications:

ASME B40.1, Grade B (\pm 3-2-3% accuracy)

Features:

PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

Construction:

Polycarbonate window
Black aluminum pointer
ABS plastic case, corrosion resistant
C-shaped bronze safety bourdon tube
Lower mount

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	GS160-4
Figure Interval	20
Minor Gradient	5
Mount	1/4"
Pressure Range	0-160 PSI
Size	3-1/2" Face
Temperature Range	-40°F to 150°F (-40°C to 65.6°C)
Weight Lb	0.3500