

## ABS STANDARD DRY GAUGE LOWER MOUNT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 02:36 AM

SKU

: 14882

BRAND

: DIXON VALVE

MODEL

: GS600-4

### Applications:

All of the gauges supplied by Dixon are designed for long, reliable service under rugged conditions. Typical applications include those on pumps, hydraulic and pneumatic systems, compressors, machine tools and many other installations where it is necessary to have a gauge with a non-corrosive movement.

### Specifications:

ASME B40.1, Grade B ( $\pm$  3-2-3% accuracy)

### Features:

PowerFlex™ movement with polyester segment, designed to resist the effects of shock, vibration and pulsation.

### Construction:

Polycarbonate window

Black aluminum pointer

ABS plastic case, corrosion resistant

C-shaped bronze safety bourdon tube

Lower mount

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	GS600-4
<b>Figure Interval</b>	50
<b>Minor Gradient</b>	10
<b>Mount</b>	1/4"
<b>Pressure Range</b>	0-600 PSI
<b>Size</b>	3-1/2" Face
<b>Temperature Range</b>	-40°F to 150°F (-40°C to 65.6°C)
<b>Weight Lb</b>	0.4545