

## STAINLESS STEEL DRY GAUGE



\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 12:13 PM

SKU  
: 14900

BRAND  
: DIXON VALVE

MODEL  
: GSS30-4

Applications:  
Provide the corrosion resistance and durability of a permanently sealed gauge

Specifications:  
1.6% accuracy, exceeds ASME B.40.100 Grade B

Construction:  
304 series stainless case  
Polycarbonate window, 3-1/2" across  
1/4" NPT lower mount stainless connector  
316L stainless bourdon tube and socket, polyester segment

Safety notes:  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	GSS30-4
<b>Figure Interval</b>	5
<b>Material</b>	Stainless Steel
<b>Minor Gradient</b>	.5
<b>Mount</b>	1/4" Lower Mount
<b>Pressure Range</b>	0-30 PSI
<b>Size</b>	4" Face
<b>Temperature Range</b>	-40°F to 140°F (-40°C to 60°C)
<b>Weight Lb</b>	0.5050