


DQC H-SERIES ISO-B HIGH VOLUME FEMALE PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/09/2026 12:42 PM

SKU
: 24453

BRAND
: DIXON VALVE

MODEL
: H10F10-SS

Construction:

Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:

Contact Dixon for all available option adders

Compatibility & Interchange Data:

Interchangeable to ISO7241 Series 'B'

Parker 60-Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1-1/4"
Burst Pressure	8500 PSI (580 bar)
Factory Part Number	H10F10-SS
Hex	2-3/8"
Length	4.25" (108.0mm)
Material	316 Stainless Steel
Maximum OD	2.60" (66.0mm)
Maximum Operating Pressure	1000 PSI (70 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)

TECHNICAL SPECIFICATIONS

Thread	Female NPTF
Thread Size	1-1/4" - 1 1/2"
Weight Lb	2.1900