


## DQC H-SERIES ISO-B HIGH VOLUME FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 12:41 PM

SKU

: 24455

BRAND

: DIXON VALVE

MODEL

: H12BF12-B

Features:

Poppet style shut-off valves

Designed to prevent fluid loss when disconnected

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:

Contact Dixon for all available option adders

Compatibility & Interchange Data:

Meets dimensional requirements of ISO 7241 Series B

Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| <b>Body Size</b>                  | 1-1/2"                            |
| <b>Burst Pressure</b>             | 6500 PSI (450 bar)                |
| <b>Factory Part Number</b>        | H12BF12-B                         |
| <b>Hex</b>                        | 2-5/8"                            |
| <b>Length</b>                     | 4.76" (120.9mm)                   |
| <b>Material</b>                   | Brass                             |
| <b>Maximum OD</b>                 | 2.88" (73.2mm)                    |
| <b>Maximum Operating Pressure</b> | 1000 PSI (70 bar)                 |
| <b>Temperature Range</b>          | -40°F to +250°F (-40°C to +121°C) |
| <b>Thread</b>                     | Female BSPP                       |
| <b>Thread Size</b>                | 1-1/2"-11                         |
| <b>Weight Lb</b>                  | 2.9600                            |