


## DQC H-SERIES ISO-B FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/22/2026 10:04 PM

SKU  
: 24471

BRAND  
: DIXON VALVE

MODEL  
: H1F1-SS

Features:  
Poppet style shut-off valves  
Designed to prevent fluid loss when disconnected

Construction:  
Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:  
Contact Dixon for all available option adders  
Oxy-Clean treatment is available

Compatibility & Interchange Data:  
Meets dimensional requirements of ISO 7241 Series B  
Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/8"
<b>Burst Pressure</b>	29500 PSI (2000 bar)
<b>Factory Part Number</b>	H1F1-SS
<b>Hex</b>	9/16"
<b>Length</b>	1.28"
<b>Material</b>	316 Stainless Steel
<b>Maximum OD</b>	0.65"
<b>Maximum Operating Pressure</b>	3500 PSI (240 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1/8"-27
<b>Weight Lb</b>	0.1800