


## DQC H-SERIES ISO-B HIGH VOLUME FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/09/2026 01:59 PM

SKU  
: 24475

BRAND  
: DIXON VALVE

MODEL  
: H20F16-B

Features:  
Poppet style shut-off valves  
Designed to prevent fluid loss when disconnected

Construction:  
Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:  
Contact Dixon for all available option adders

Compatibility & Interchange Data:  
Meets dimensional requirements of ISO 7241 Series B  
Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	2-1/2"
<b>Burst Pressure</b>	5500 PSI (380 bar)
<b>Factory Part Number</b>	H20F16-B
<b>Hex</b>	3-3/4"
<b>Length</b>	5.48" (139.2mm)
<b>Material</b>	Brass
<b>Maximum OD</b>	4.10" (104.1mm)
<b>Maximum Operating Pressure</b>	700 PSI (50 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	2" - 11-1/2
<b>Weight Lb</b>	8.1600