

## DQC H-SERIES ISO-B MALE PLUG



DATE  
: 07/09/2026 01:58 PM

SKU  
: 24487

BRAND  
: DIXON VALVE

MODEL  
: H2M3

Features:  
Poppet style shut-off valves  
Designed to prevent fluid loss when disconnected

Construction:  
Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.  
Steel componentry is plated using ROHS Compliant Trivalent Chrome.  
Steel Nipples are hardened to provide heavy duty performance and resist brinelling.

Available Options:  
Contact Dixon for all available option adders

Compatibility & Interchange Data:  
Meets dimensional requirements of ISO 7241 Series B  
Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	1/4"
<b>Burst Pressure</b>	22500 PSI (1550 bar)
<b>Factory Part Number</b>	H2M3
<b>Hex</b>	3/4"
<b>Length</b>	2.03" (51.6mm)
<b>Material</b>	Steel
<b>Maximum OD</b>	0.83" (21.1mm)
<b>Maximum Operating Pressure</b>	5000 PSI (345 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Male NPTF
<b>Thread Size</b>	3/8"-18
<b>Weight Lb</b>	0.1050