


## DQC H-SERIES ISO-B FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/22/2026 10:52 PM

SKU  
: 24507

BRAND  
: DIXON VALVE

MODEL  
: H3F3-B

**Features:**

Poppet style shut-off valves

Designed to prevent fluid loss when disconnected

**Construction:**

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

**Available Options:**

Contact Dixon for all available option adders

Oxy-Clean treatment is available

**Compatibility & Interchange Data:**

Meets dimensional requirements of ISO 7241 Series B

Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

**Safety notes:**

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	3/8"
<b>Burst Pressure</b>	12000 PSI (800 bar)
<b>Factory Part Number</b>	H3F3-B
<b>Hex</b>	7/8"
<b>Length</b>	1.70" (43.2mm)
<b>Material</b>	Brass
<b>Maximum OD</b>	0.97" (24.6mm)
<b>Maximum Operating Pressure</b>	3000 PSI (200 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	3/8"-18
<b>Weight Lb</b>	0.1400