


DQC H-SERIES ISO-B FEMALE PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/22/2026 10:52 PM

SKU

: 24514

BRAND

: DIXON VALVE

MODEL

: H4BF4-B

Features:

Poppet style shut-off valves

Designed to prevent fluid loss when disconnected

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:

Contact Dixon for all available option adders

Oxy-Clean treatment is available

Compatibility & Interchange Data:

Meets dimensional requirements of ISO 7241 Series B

Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------------------|
| Body Size | 1/2" |
| Burst Pressure | 11500 PSI (750 bar) |
| Factory Part Number | H4BF4-B |
| Hex | 1-1/16" |
| Length | 1.94" (49.3mm) |
| Material | Brass |
| Maximum OD | 1.17" (29.7mm) |
| Maximum Operating Pressure | 2500 PSI (170 bar) |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |
| Thread | Female BSPP |
| Thread Size | 1/2"-14 |
| Weight Lb | 0.2500 |