

DQC H-SERIES ISO-B FEMALE PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/22/2026 10:53 PM

SKU

: 24515

BRAND

: DIXON VALVE

MODEL

: H4BF4-S

Features:

Poppet style shut-off valves

Designed to prevent fluid loss when disconnected

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:

Contact Dixon for all available option adders

Oxy-Clean treatment is available

Compatibility & Interchange Data:

Meets dimensional requirements of ISO 7241 Series B

Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	27500 PSI (1900 bar)
Factory Part Number	H4BF4-S
Hex	1-1/16"
Length	1.94" (49.3mm)
Material	303 Stainless Steel
Maximum OD	1.17" (29.7mm)
Maximum Operating Pressure	3500 PSI (240 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female BSPP
Thread Size	1/2"-14
Weight Lb	0.2400