

## DQC H-SERIES ISO-B FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/09/2026 10:29 AM

SKU  
: 24516

BRAND  
: DIXON VALVE

MODEL  
: H4BF4-SS

Features:  
Poppet style shut-off valves  
Designed to prevent fluid loss when disconnected

Construction:  
Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:  
Contact Dixon for all available option adders  
Oxy-Clean treatment is available

Compatibility & Interchange Data:  
Meets dimensional requirements of ISO 7241 Series B  
Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

|                                   |                                   |
|-----------------------------------|-----------------------------------|
| <b>Body Size</b>                  | 1/2"                              |
| <b>Burst Pressure</b>             | 22000 PSI (1500 bar)              |
| <b>Factory Part Number</b>        | H4BF4-SS                          |
| <b>Hex</b>                        | 1-1/16"                           |
| <b>Length</b>                     | 1.94" (49.3mm)                    |
| <b>Material</b>                   | 316 Stainless Steel               |
| <b>Maximum OD</b>                 | 1.17" (29.7mm)                    |
| <b>Maximum Operating Pressure</b> | 3500 PSI (240 bar)                |
| <b>Temperature Range</b>          | -40°F to +250°F (-40°C to +121°C) |
| <b>Thread</b>                     | Female BSPP                       |
| <b>Thread Size</b>                | 1/2"-14                           |
| <b>Weight Lb</b>                  | 0.2300                            |