

DUBL-GRIP® FIELD ATTACHABLE COUPLING FOR CURB PUMP HOSE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 12:50 AM

SKU

: 24575

BRAND

: DIXON VALVE

MODEL

: H605

Specifications:

UL recognized

Fluid Hose number MH49909

Features:

Two-piece field attachable coupling

Streamlined design prevents damage to hose and fits well on new pump equipment.

Wide, flat surfaces of body threads protect inside of hose from breaking.

Tapered surfaces of sleeve and body cradle hose, prevent one-point strain from flexing.

Hose is gripped on its full circumference in two places, ensuring a rigid leak-proof connection.

Couplings have standard male NPT threads

Installation

Easy assembly: hose is held in position by sleeve as body is threaded home, only a wrench is required to assemble the DUBL-Grip®.

Safety notes:

Reattach static wire if required.

Hose service working pressure (including surges and spikes) is never to exceed the maximum recommended working pressure for the fitting. The assembly's (hose + coupling) maximum working pressure is the lesser of the hose rated working pressure or the coupling rated working pressure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	H605
Hose ID	3/4"
Hose OD	1-1/4"
Material	Chrome Plated Brass
Thread	NPT
Thread Size	3/4"
Weight Lb	0.5000