

**NITRILE COVERED FIRE HOSE  
HEAVY DUTY**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/23/2026 08:51 PM

SKU

: 14983

BRAND

: DIXON VALVE

MODEL

: H625Y50UC

Applications:

Ideal for heavy-duty washdown, refineries and power plants

Construction:

Outer: Yellow, Thick Ribbed Nitrile

Tube: Nitrile

Safety notes:

Under no circumstance should the hose be used beyond the working pressure of the fittings to which it is coupled.

Assembled hose should be hydrostatically proof tested before use, and thereafter in accordance with NFPA 1962.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Bowl Size</b>	2-13/16"
<b>Color</b>	Yellow
<b>Coupling Type</b>	Uncoupled
<b>Factory Part Number</b>	H625Y50UC
<b>Hose Size</b>	2-1/2"
<b>Proof Pressure</b>	600 PSI
<b>Service Test Pressure</b>	300 PSI
<b>Weight Lb</b>	28.0000
<b>Working Pressure</b>	270 PSI