

## DQC H-SERIES ISO-B FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/09/2026 11:27 AM

SKU  
: 24599

BRAND  
: DIXON VALVE

MODEL  
: H8F8-S

### Features:

Poppet style shut-off valves

Designed to prevent fluid loss when disconnected

### Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

### Available Options:

Contact Dixon for all available option adders

Oxy-Clean treatment is available

### Compatibility & Interchange Data:

Meets dimensional requirements of ISO 7241 Series B

Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1"
<b>Burst Pressure</b>	15000 PSI (1000 bar)
<b>Factory Part Number</b>	H8F8-S
<b>Hex</b>	1-5/8"
<b>Length</b>	2.87" (72.9mm)
<b>Material</b>	303 Stainless Steel
<b>Maximum OD</b>	1.79" (45.5mm)
<b>Maximum Operating Pressure</b>	2000 PSI (138 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1" - 11-1/2
<b>Weight Lb</b>	0.7500