


DQC H-SERIES ISO-B FEMALE PLUG



DATE
: 05/23/2026 12:34 AM

SKU
: 24599

BRAND
: DIXON VALVE

MODEL
: H8F8-S

Features:

Poppet style shut-off valves

Designed to prevent fluid loss when disconnected

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Available Options:

Contact Dixon for all available option adders

Oxy-Clean treatment is available

Compatibility & Interchange Data:

Meets dimensional requirements of ISO 7241 Series B

Interchangeable with Parker-Hannifin 60 Series, Snap-Tite 72-Series, Hansen HK-Series, Faster Series 'HNV', Aeroquip/Eaton FD45, Stucchi Series IRB/IRBO/IRBX

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------------------|
| Body Size | 1" |
| Burst Pressure | 15000 PSI (1000 bar) |
| Factory Part Number | H8F8-S |
| Hex | 1-5/8" |
| Length | 2.87" (72.9mm) |
| Material | 303 Stainless Steel |
| Maximum OD | 1.79" (45.5mm) |
| Maximum Operating Pressure | 2000 PSI (138 bar) |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |
| Thread | Female NPTF |
| Thread Size | 1" - 11-1/2 |
| Weight Lb | 0.7500 |