

## CAM & GROOVE HASTELLOY® TYPE B COUPLER X MALE NPT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 07:32 PM

SKU

: 15064

BRAND

: DIXON VALVE

MODEL

: HAB200EZ

Applications:

Designed for use with liquids, consult Dixon for specific recommendations

Specifications:

Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Construction:

316 stainless steel EZ Boss-Lock™ cam arms

302 stainless steel pins

Yellow zinc plated 12 gauge steel wire rings

Supplied with FKM-A gasket

How it works:

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Under no circumstances should the EZ Boss-Lock cam arms be used on any fitting not specifically designed for their use.

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Material</b>	Hastelloy® CW12MW
<b>Maximum Operating Pressure</b>	250 PSI
<b>Factory Part Number</b>	HAB200EZ
<b>Seal</b>	FKM-A
<b>Size</b>	2"
<b>Weight Lb</b>	2.3500