


## DQC HS-SERIES ISO-B STEAM INTERCHANGE FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/09/2026 08:21 PM

SKU  
: 24637

BRAND  
: DIXON VALVE

MODEL  
: HS3BF3-B

Applications:  
Designed exclusively for steam applications

Construction:  
Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.  
Special high-temp EPDM O-rings designed for steam service

Compatibility & Interchange Data:  
Interchangeable to ISO7241 Series 'B'  
Parker 60-Series Steam Couplings

Safety notes:  
Maximum working pressure has been calculated using standard saturated steam at 194°C (382°F) for general purpose continuous service. For advanced operating pressure or super-heated steam applications, contact Dixon for further information.

Warning: Do not disconnect under pressure!

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                            |  |
|----------------------------|--|
| <b>Body Size</b>           | 3/8"   |
| <b>Factory Part Number</b> | HS3BF3-B   |
| <b>Hex</b>                 | 7/8"   |
| <b>Length</b>              | 1.70" (43.2 mm)                                      |
| <b>Material</b>            | Brass  |
| <b>Maximum OD</b>          | 0.97" (24.6 mm)                                      |
| <b>Pressure Rating</b>     | Rated to 200 PSI gauge saturated steam 382°F (194°C) |
| <b>Temperature Range</b>   | -70°F to +400°F (-57°C to +204°C)                    |
| <b>Thread</b>              | Female BSPP  |
| <b>Thread Size</b>         | 3/8"-19  |