

DQC HS-SERIES ISO-B STEAM INTERCHANGE FEMALE PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/23/2026 08:59 AM

SKU

: 24636

BRAND

: DIXON VALVE

MODEL

: HS3BF3

Applications:

Designed exclusively for steam applications

Construction:

Machined components are manufactured using solid bar stock

Steel nipples are hardened to provide heavy duty performance and resist brinelling.

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Special high-temp EPDM O-rings designed for steam service

Compatibility & Interchange Data:

Interchangeable to ISO7241 Series 'B'

Parker 60-Series Steam Couplings

Safety notes:

Maximum working pressure has been calculated using standard saturated steam at 194°C (382°F) for general purpose continuous service. For advanced operating pressure or super-heated steam applications, contact Dixon for further information.

Warning: Do not disconnect under pressure!

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Factory Part Number	HS3BF3
Hex	7/8"
Length	1.70" (43.2 mm)
Material	Steel
Maximum OD	0.97" (24.6 mm)
Pressure Rating	Rated to 200 PSI gauge saturated steam 382°F (194°C)
Temperature Range	-70°F to +400°F (-57°C to +204°C)
Thread	Female BSPP
Thread Size	3/8"-19
Weight Lb	0.1200