

HSC SERIES SPRING CHECK VALVE



DATE
: 05/03/2026 01:09 AM

SKU
: 15419

BRAND
: DIXON VALVE

MODEL
: HSCV200

Applications:
Spring check valves are designed to prevent reverse flow. The concentric design makes them ideal for vertical applications.

Features:
Single piece upper body spider design
Machined from solid bar
Standard O-ring and gasket seal design
Can be serviced in field (no special tools required)
Finish: sanitary polish 32 Ra

Available Options:
Various end connections available

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|----------------------|
| Cracking Pressure | 1.5 PSI |
| Elastomer | FKM |
| Material | 316L Stainless Steel |
| Maximum Operating Pressure | 145 PSI |
| Optional Pkg/Box Qty | 1 |
| Factory Part Number | HSCV200 |
| Size | 2" |
| Style | Clamp Connection |

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

| | |
|--------------------------|--------------------------------|
| Temperature Range | 15°F to 200°F (-9.4°C to 93°C) |
| Weight Lb | 2.2000 |