

## DQC HT-SERIES FLUSHFACE FEMALE THREADED PLUG



DATE  
: 05/23/2026 03:18 PM

SKU  
: 15630

BRAND  
: DIXON VALVE

MODEL  
: HT6F8-SS

### Specifications:

Rated pressure for connected 316 Stainless Steel Coupler and 316 Stainless Steel Plug: 2,920 PSI (201 bar) Maximum Working and 14,600 PSI (1,007 bar) burst

### Features:

High flow performance, compact profile

Easily rebuildable!

High strength laser-cut valve guide maximizes valve stability while minimizing flow restriction.

Improved sealing system incorporates a high performance molded polyurethane or O-ring energized PTFE valve seal.

### Construction:

Machined components are manufactured using solid bar stock

Has molded Polyurethane valve seals, with a temperature range of -65° to +212°F

Ancillary nipple seals are Nitrile (Buna-N), with a temperature range of -40°F to +250°F

PTFE or TPC-ET Anti-Extrusion ring protects main coupling valve seal from dynamic impulse pressure damage.

### Available Options:


Contact Dixon for all available option adders

Oxy-clean treatment is available

### Compatibility & Interchange Data:

Interchangeable to ISO16028

Conforms to ISO16028 interchange standard interchangeable with Eaton/Hansen FF, Parker FEM, Snap-tite 74, Faster FFH/2FFN/2FFI, Stucchi A/FIRG and Holmbury HQ/A/FIMC



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	3/4"
<b>Factory Part Number</b>	HT6F8-SS
<b>Hex</b>	1-3/4"
<b>Length</b>	3.54" (89.9mm)
<b>Material</b>	316 Stainless Steel
<b>Maximum OD</b>	1.92" (48.8mm)
<b>Pressure Rating</b>	See Product Details
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1" - 11-1/2
<b>Weight Lb</b>	1.1500