

DIXON® FEMALE FRAC FITTING



DATE
: 07/08/2026 10:53 PM

SKU
: 15796

BRAND
: DIXON VALVE

MODEL
: HUF100400CS

Applications:

Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

Use:

Designed to work with Dixon King Crimp Ferrules.

Features:

One-piece design eliminates leak path experienced with two-piece threaded systems

Durable and safe with reliable hose retention when crimped as specified

Construction:

Machined Iron to ASTM standards

All stems are zinc plated

Compatibility & Interchange Data:

Interchangeable with current fittings; phase them into your current operation

Note:

Water and petroleum transfer hoses rated from 100 to 300 PSI WP (4:1 SF) have excellent test results with the standard King Crimp ferrules CF400-xxCS)

Safety notes:

400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 4" size requires heavy duty (HD) crimp ferrules, CF400-6CSHD through CF400-16CSHD and heavy duty stems
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	HUF100400CS
Material	Iron
Size	4"
Style	Figure 100
Weight Lb	10.4500
Working Pressure	400 PSI at 70°F (21°C)