

## DIXON® FEMALE FRAC FITTING



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability



DATE  
: 07/08/2026 10:54 PM

SKU  
: 15797

BRAND  
: DIXON VALVE

MODEL  
: HUF206200CS

### Applications:

Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

### Use:

Designed to work with Dixon King Crimp Ferrules.

### Features:

One-piece design eliminates leak path experienced with two-piece threaded systems

Durable and safe with reliable hose retention when crimped as specified

### Construction:

Machined Iron to ASTM standards

All stems are zinc plated

### Compatibility & Interchange Data:

Interchangeable with current fittings; phase them into your current operation

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 2" sizes using standard crimp ferrules

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	HUF206200CS
<b>Material</b>	Iron
<b>Size</b>	2"
<b>Style</b>	Figure 200/206
<b>Weight Lb</b>	2.0500
<b>Working Pressure</b>	400 PSI at 70°F (21°C)