

## DIXON® FEMALE FRAC FITTING



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability



DATE  
: 04/04/2026 11:38 PM

SKU  
: 15800

BRAND  
: DIXON VALVE

MODEL  
: HUF206400CS

### Applications:

Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

### Use:

Designed to work with Dixon King Crimp Ferrules.

### Specifications:

Machined malleable iron stems to ASTM A47 standard

### Features:

One-piece design eliminates leak path experienced with two-piece threaded systems

Long lasting and dependable hammer nut is forged to ASTM 105N standards

### Construction:

Machined iron to ASTM standards; all stems are zinc plated

### Compatibility & Interchange Data:

Interchangeable with current fittings; phase them into your current operation

### Note:

Water and petroleum transfer hoses rated from 100 to 300 PSI WP (4:1 SF) have excellent test results with the standard King Crimp ferrules CF400-xxCS)

### Safety notes:

400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 4" size requires heavy duty (HD) crimp ferrules, CF400-6CSHD through CF400-16CSHD and heavy duty stems

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	HUF206400CS
<b>Material</b>	Iron
<b>Size</b>	4"
<b>Style</b>	Figure 200/206
<b>Weight Lb</b>	8.7500
<b>Working Pressure</b>	400 PSI at 70°F (21°C)