

DIXON® FEMALE FRAC FITTING



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/22/2026 09:13 AM

SKU
: 15800

BRAND
: DIXON VALVE

MODEL
: HUF206400CS

Applications:

Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

Use:

Designed to work with Dixon King Crimp Ferrules.

Specifications:

Machined malleable iron stems to ASTM A47 standard

Features:

One-piece design eliminates leak path experienced with two-piece threaded systems

Long lasting and dependable hammer nut is forged to ASTM 105N standards

Construction:

Machined iron to ASTM standards; all stems are zinc plated

Compatibility & Interchange Data:

Interchangeable with current fittings; phase them into your current operation

Note:

Water and petroleum transfer hoses rated from 100 to 300 PSI WP (4:1 SF) have excellent test results with the standard King Crimp ferrules CF400-xxCS)

Safety notes:

400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 4" size requires heavy duty (HD) crimp ferrules, CF400-6CSHD through CF400-16CSHD and heavy duty stems

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	HUF206400CS
Material	Iron
Size	4"
Style	Figure 200/206
Weight Lb	8.7500
Working Pressure	400 PSI at 70°F (21°C)