

## DIXON® FEMALE FRAC FITTING



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability



DATE  
: 05/22/2026 09:12 AM

SKU  
: 15804

BRAND  
: DIXON VALVE

MODEL  
: HUFALL600CS

### Applications:

Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

### Use:

Designed to work with Dixon King Crimp Ferrules.

### Features:

One-piece design eliminates leak path experienced with two-piece threaded systems

Durable and safe with reliable hose retention when crimped as specified

### Construction:

Machined Iron to ASTM standards

All stems are zinc plated

### Compatibility & Interchange Data:

Interchangeable with current fittings; phase them into your current operation

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

230 PSI working pressure with a minimum 4:1 safety factor 6" sizes using standard crimp ferrules

Pressure rating is given at 70°F/21°C

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	HUFALL600CS
<b>Material</b>	Iron
<b>Size</b>	6"
<b>Style</b>	Figure 100/200/206
<b>Weight Lb</b>	27.1000
<b>Working Pressure</b>	230 PSI at 70°F (21°C)