

DIXON® MALE FRAC FITTING WITH NUT



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 07/08/2026 11:48 PM

SKU
: 15810

BRAND
: DIXON VALVE

MODEL
: HUM100600CS

Applications:

Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

Use:

Designed to work with Dixon King Crimp Sleeves or Ferrules.

Features:

One-piece design eliminates leak path experienced with two-piece threaded systems

Construction:

Frac fittings: machined iron to ASTM standards; zinc plated

Nut: forged steel meeting AISI standards

Figures 100 and 200 have a metal-to-metal sealing surface; Figure 206 is similar to Figure 200 with a secondary seal to supplement the metal-to-metal design.

Compatibility & Interchange Data:

Interchangeable with current fittings; phase them into your current operation

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

230 PSI working pressure with a minimum 4:1 safety factor 6" sizes using standard crimp ferrules

Pressure rating is given at 70°F/21°C

TECHNICAL SPECIFICATIONS

Description	Male fitting
Factory Part Number	HUM100600CS
Includes	Nut
Mandatory Pkg/Box Qty	1
Material	Forged steel nut, Iron Fitting
Seal	Metal-to-metal
Size	6"
Style	Figure 100
Weight Lb	42.3000
Working Pressure	230 PSI at 70°F (21°C)