

## DIXON® MALE FRAC FITTING WITH NUT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/08/2026 11:48 PM

SKU  
: 15812

BRAND  
: DIXON VALVE

MODEL  
: HUM206200CS

### Applications:

Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

### Use:

Designed to work with Dixon King Crimp Sleeves or Ferrules.

### Features:

One-piece design eliminates leak path experienced with two-piece threaded systems

Long lasting and dependable forged hammer nut

Durable and safe with reliable hose retention when crimped as specified

### Construction:

Frac fittings: machined iron to ASTM standards; zinc plated

Nut: forged steel meeting AISI standards

Buna-N O-ring (O228BU)

Figures 100 and 200 have a metal-to-metal sealing surface; Figure 206 is similar to Figure 200 with a secondary seal to supplement the metal-to-metal design.

### Compatibility & Interchange Data:

Interchangeable with current fittings; phase them into your current operation

### Safety notes:

400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 3" sizes uses standard crimp stem

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Description</b>	Male fitting
<b>Factory Part Number</b>	HUM206200CS
<b>Includes</b>	Nut, O-ring
<b>Mandatory Pkg/Box Qty</b>	1
<b>Material</b>	Forged steel nut, Iron fitting
<b>Seal</b>	Buna-N
<b>Size</b>	2"
<b>Style</b>	Figure 206
<b>Weight Lb</b>	4.3500
<b>Working Pressure</b>	400 PSI at 70°F (21°C)