

## DIXON® COMPLETE ASSEMBLY FRAC FITTING



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/22/2026 09:13 AM

SKU  
: 15825

BRAND  
: DIXON VALVE

MODEL  
: HUMF206200CS

### Applications:

Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

### Use:

Designed to work with Dixon King Crimp Ferrules.

### Features:

One-piece design eliminates leak path experienced with two-piece threaded systems

Long lasting and dependable forged hammer nut

Durable and safe with reliable hose retention when crimped as specified

### Construction:

Frac fittings: machined iron to ASTM standards; zinc plated

Nut: forged steel meeting AISI standards

Painted Carbon Steel forged nut

Buna-N Oring (O228BU)

Figure 200 has a metal-to-metal sealing surface and Figure 206 is similar to Figure 200 with a secondary seal to supplement the metal-to-metal design.

### Compatibility & Interchange Data:

Interchangeable with current fittings; phase them into your current operation

### Safety notes:

400 PSI working pressure with a minimum 4:1 safety factor (hose burst: hose working pressure) is only achieved with: 2" and 3" sizes using standard crimp ferrules

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Description</b>	Male/female complete assembly
<b>Factory Part Number</b>	HUMF206200CS
<b>Mandatory Pkg/Box Qty</b>	1
<b>Material</b>	Iron/Steel
<b>Size</b>	2"
<b>Style</b>	Figure 206
<b>Weight Lb</b>	6.4000
<b>Working Pressure</b>	400 PSI at 70°F (21°C)