

DIXON® COMPLETE ASSEMBLY FRAC FITTING



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability



DATE
: 05/12/2026 10:48 AM

SKU
: 15833

BRAND
: DIXON VALVE

MODEL
: HUMF206800CS

Applications:

Used in the fast paced transfer of water and sand slurry at hydraulic fracturing sites.

Use:

Designed to work with Dixon King Crimp Ferrules.

Features:

One-piece design eliminates leak path experienced with two-piece threaded systems

Long lasting and dependable forged hammer nut

Durable and safe with reliable hose retention when crimped as specified

Construction:

Frac fittings: machined iron to ASTM standards; zinc plated

Nut: forged steel meeting AISI standards

Painted Carbon Steel forged nut

Buna-N Oring (O447BU)

Figure 200 has a metal-to-metal sealing surface and Figure 206 is similar to Figure 200 with a secondary seal to supplement the metal-to-metal design.

Compatibility & Interchange Data:

Interchangeable with current fittings; phase them into your current operation

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov
150 PSI at 70°F (21°C) 3:1 safety factor

TECHNICAL SPECIFICATIONS

Description	Male/female complete assembly
Factory Part Number	HUMF206800CS
Mandatory Pkg/Box Qty	1
Material	Iron/Steel
Size	8"
Style	Figure 206
Weight Lb	93.0000
Working Pressure	150 PSI at 70°F (21°C)